

D4s Settings

03.12.14

## **PLAYBACK MENU**

Delete

Playback folder – ALL

Hide image

Playback display options > Basic photo info > Highlights  
>Shooting data  
>Overview

Copy images(s)

Image review - OFF

After delete > Show previous

Rotate tall – OFF

## **SHOOTING MENU**

Shooting menu bank – A

Extended menu banks – OFF

Storage folder – 100

File naming – BMP

Primary slot selection > CF

Secondary slot function > Overflow

Image quality > Raw

JPEG/TIFF recording >Image size L  
>JPEG compression > Optimal quality

NEF (RAW) recording >Image size > L  
> NEF (RAW) compression > Lossless compressed  
> NEF (RAW) bit depth > 14-bit

Image area > Choose image area > FX  
> Auto DX crop > ON

White balance > AUTO1 (is my default, switched when needed)

Set Picture Control > Standard > Sharpening 5  
> Vivid > Sharpening 5  
> Landscape > Sharpening 5

Manage Picture Control

Color Space > Adobe RGB

Active D-Lighting – OFF

HDR (high dynamic range) OFF

Vignette control – N

Auto distortion control – ON

Long exposure NR – OFF

High ISO NR – OFF

ISO sensitivity settings > 100  
> Auto ISO sensitivity control – OFF

Multiple exposure – OFF

Interval timer shooting – OFF

Live view photography > Quiet

Time-lapse photography – OFF

Movie settings > Frame size/frame rate > 1080/60

> Movie quality > HIGH

> Microphone > 11

> Frequency response > voice

> Wind noise reduction . OFF

> Destination > XQD

> ISO sensitivity range > ISO sensitivity (mode M) 200

> Auto ISO control (mode M) ON

> Maximum sensitivity > 25600

## **CUSTOM SETTING MENU**

Custom settings bank – A

a Autofocus

a1\* AF-C priority selection – focus

a2 AF-S priority selection – focus

a3 Focus tracking with lock-on > 3 (Normal)

a4 AF activation – ON

a5\* Focus point illumination > Manual focus mode > ON

> Continuous mode > ON

> Focus point brightness > 1 (High)

> Dynamic-area AF display > ON

> Group-area AF illumination > dots

a6\*Focus point wrap-around > ON

a7 Number of focus points > AF51

a8 Assign AF-ON button > AF-ON

a9 Assign AF-ON button (vert.) > AF-ON

a10\*Store by orientation > Focus point

a11\* Limit AF-area mode selection > Dynamic-area AF (21 point)

> Group-area AF

> Auto-area AF

a12 Autofocus mode restrictions > OFF

b Metering/exposure

b1 ISO sensitivity step value > 1/3

b2 EV steps for exposure cntrl > 1/3

b3 Exp./flash comp. step value > 1/3

b4 Easy exposure compensation – OFF

b5\* Matrix metering > Face detection on

b6 Center-weighted area – (●)12

b7 Fine-tune optimal exposure --

c Timers/AE lock

c1 Shutter-release button AE-L – OFF

c2 Standby timer – 6s

c3 Self-timer --

c4 Monitor off delay --

#### d Shooting/display

- d1 Beep --
- d2 Continuous shooting speed --
- d3 Max. continuous release 200
- d4 Exposure delay mode – OFF
- d5 File number sequence – ON
- d6\*Viewfinder grid display – ON
- d7\*Control panel/viewfinder > Rear control panel > Exposures remaining  
> Viewfinder display > Frame count
- d8 Screen tips – ON
- d9 Information display – AUTO
- d10 LCD illumination – OFF

#### e Bracketing/flash

- e1\*Flash sync speed > 1/250\*
- e2\*Flash shutter speed > 1/15
- e3 Optional flash
- e4\*Exposure comp. for flash > Background only
- e5 Modeling flash – ON
- e6 Auto bracketing set – AE & flash
- e7 Auto bracketing (Mode M) – Flash/speed
- e8\*Bracketing order > Under>MTR>over

#### f Controls

- f1\*Multi selector center button > Shooting mode > RESET  
> Playback mode > Zoom on/off > Low magnification (50%)  
> Live view > RESET
- f2 Multi selector > OFF
- f3\*Assign Fn button > Press > Flash Disable/enable
- f4\*Assign preview button > Press > Viewfinder virtual horizon
- f5 Assign sub-selector – Focus point selection
- f6\* Assign sub-selector center > none
- f7\* Assign Fn button (vert.) --
- f8 Shutter spd & aperture lock --
- f9 Assign BKT button – BKT
- f10\*Customize command dials > Reverse rotation > Exposure compensation  
> Shutter speed/aperture  
> Change main/sub > --  
> Aperture setting > ON  
> Menus and playback > ON  
> Sub-dial frame advance > 10
- f11 Release button to use dial – OFF
- f12 Slot empty release lock – OK
- f13 Reverse indicators > – 0 +
- f14 Assign multi selector (vert.) – Same as multi selector
- f15 Playback zoom > + & - buttons
- f16\* Assign movie record button > Choose Image Area > FX  
> DX

f17 Live view button options > ON  
f18 Assign remote (WR) Fn button > OFF  
f19\* Lens focus function buttons > AF Area Mode

#### g Movie

g1 Assign Fn button – OFF  
g2\* Assign preview button > Press > Power aperture  
g3 Assign sub-selector center > Press > AE/AF lock  
g4\* Assign shutter button > Record movies

#### SETUP MENU

Format memory card --  
Monitor brightness – 0  
Monitor color balance --  
Clean image sensor > Clean at startup/shutdown  
Lock mirror up for cleaning --  
Image Dust Off ref photo --  
Flicker reduction > AUTO  
Time zone and date – (always set to current location)  
Language – English  
Auto image rotation – ON  
Battery info --  
Image comment – OFF  
Copyright information – ON  
IPTC  
Voice memo options --  
Save/load settings --  
Virtual horizon --  
Non-CPU lens data – No.1  
AF fine-tune --  
HDMI > Output resolution > Auto  
    > Advanced > Output range > Auto  
        > Output display size > 100%  
        > Live view on-screen display > ON  
        > Dual monitor > ON  
Location data –  
Network --  
Firmware version --

#### MY MENU

Time zone and date  
B5 Matrix metering  
Time-lapse photography  
C3 Self-timer  
Movie quality  
Microphone sensitivity  
Lock mirror up for cleaning

blank = default

\* = modified